













ZESTAWIENIE STOLARKI OKIENNEJ					
ILOŚĆ	SYMBOL	WYMIAR W ŚWIETLE MURU		SCHEMAT	UWAGI
		So	Ho		
2	90/ 60	90	60		-
1	80/ 140	80	140		-
1	90/ 145	90	145		-
9	150/ 145	150	145		-

ZESTAWIENIE STOLARKI DRZWIOWEJ										
										
WYMIARY W ŚWIETLE MURU (cm)		Sz	236	100	100	90	150	100	100	90
		Hs	235	235	210	210	210	205	205	205
WYMIARY ZEWN. OŚCIEŻNICY (cm)		So	150 + nasświetle	90	90	80	140	90	90	86
		Ho	225	225	198	198	203	198	198	190
ILOŚĆ (szt.)	PARTER		1 szt. (1P)	3 szt. (2P+1L)	2 szt. (2L)	3 szt. (2P+1L)	1 szt. (1P)	1 szt. (1L)	3 szt. (1P+2L)	4 szt. (4P)
RODZAJ:			Zewnętrzne	Zewnętrzne	Zewnętrzne	Zewnętrzne	Wewnętrzne	Wewnętrzne	Wewnętrzne	Wewnętrzne
UWAGI:			Drzwi aluminiowe z nasświetlaniem bocznym	Drzwi aluminiowe przeszklone	Drzwi stalowe	Drzwi stalowe	Drzwi aluminiowe przeszklone	Drzwi stalowe	Skrzydło drzwiowe łazienkowe z kratką wentylacyjną	Drzwi łazienkowe systemowe z kratką wentylacyjną